

Data Sheet

FUJITSU Display P34-9 US

Ultrawide Curved 34 inch (86.3 cm) high performance Display
One that fits for all - our new wave of innovation!

The ultrawide FUJITSU Display P34-9 US comes with a brilliant 3440x1440 resolution and a 1900R curvature. With the wide viewing angle and its almost bezelfree housing, it meets the requirements of various usage scenarios

34-inch with 21:9 aspect ratio at UWQHD resolution for consistent clarity and superior viewing experience

KVM function for common use of peripheral hardware for new connected USB type-C devices makes it ideal for Shared Desk. The integrated built-in port replicator enables power delivery with only one USB Type-C cable to reduce cable clutter for a clean desk approach

Outstanding Secure due to unique FUJITSU Presence Sensor with active PC-lock function to meet even high data protection requirements in certain business segments

Next generation IPS reduce response time as low as 1ms and advanced colors space match 98% DCI-P3 that provides perfect media consumption as creation. Combined with AMD Free sync support, it's perfect to enjoy videos and gaming on highest level

All in One: Videos out of two sources can be shown simultaneously by using PIP (picture-in-picture) or PBP (picture by picture) function

DisplayView™ software enables easy monitor configuration for adjusting screen brightness, screen splitting and much more for an optimized workspace with increased productivity

Environmental-friendly LED technology with highly efficient energy saving functions like ECO Operation mode and ECO standby helping you save on costs

Ongoing product improvement: One-Click firmware upgrade by end user opens the chance to get more and better features for already installed displays



Technical details

Special features

Smart Power ON and LED function for AiO-type usage (in combination with a dedicated FUJITSU PC e.g. ESPRIMO G), DICOM Greyscale Standard Display Function compatible gamma preset, Eco button for Eco mode and 4-colored status LED, Presence sensor with PC security solution, In-Plane Switching (IPS) technology, Color accuracy average DeltaE<2, Auto Brightness Control (ABC), Workplace Lighting Guide, DisplayView™ Software, Cable guide, Auto Pivot, Always available USB (in operating and standby mode), 24/7 usage, Integrated speakers, 4-in-1 Stand

Ergonomic stand

Stand	4-in-1 Stand
Height adjust range	130 mm
Picture height over desk (min)	40 mm
Tilt angle	-4° / +34°
Swivel angle	345°

Picture performance

Panel and backlight	In-Plane Switching (IPS) technology/LED
Screen Surface Treatment	Anti-glare, 3H hard coating
Contrast - typical	1,000:1
Contrast - advanced	20,000,000:1
Response time gray to gray typical	5 ms (in Video mode)
Viewing angle (h/v) - typical	178°/178° CR10:1
Color performance	1.07 billion (8bit + A-FRC)
Brightness - typical	400 cd/m ²

Size and resolution

Aspect ratio	21:9
Diagonal Size	86.3 cm (34 inch)
Curvature	R1,900
Resolution (native)	3,440 x 1,440 pixel
Resolution (interpolated)	2,560 x 1,440 pixel, 2,560 x 1,080 pixel, 1,920 x 1,200 pixel, 1,920 x 1,080 pixel, 1,680 x 1,050 pixel, 1,600 x 900 pixel, 1,440 x 900 pixel, 1,280 x 1,024 pixel, 1,280 x 720 pixel, 1,024 x 768 pixel, 800 x 600 pixel, 640 x 480 pixel
Picture size	800 x 335 mm
Pixel Pitch	0.2325 mm

Frequencies

Horizontal	30 - 160 kHz
Vertical	28 - 102 Hz

Connectivity

DisplayPort	1 x DisplayPort Out (Daisy Chain), 1 x DisplayPort 1.2
HDMI	2 x HDMI 2.0
Audio signal output	3.5 mm stereo phone jack for head phone
Audio sound output	2 x 3 W
USB downstream	4 x USB 3.2 Gen1 (2 side USB: 1x Type A + 1x Type C; 2 bottom USB: Type A)
USB upstream	1 x USB-C with alternate mode for video data and power delivery up to 65W (USB 2.0 performance in combination with DaisyChain) 1 x USB 3.2 Gen1 Type B Integrated KVM switch function

Ease-of-use menu

Notes	6 tactile keys on front side
Direct Access Keys	Brightness, ECO, Input, Mode, Audio, Menu
Languages	Arabic, Czech, Danish, Dutch, English, Finnish, French, German, Italian, Norwegian, Polish, Portuguese, Russian, Spanish, Swedish, Turkish, Japanese, Chinese simply, Chinese traditional
Brightness / Contrast	Brightness, Contrast, Black level, Auto Brightness, ACR, Lighting Guide
Mode	sRGB, Office, Photo, Video, Low Blue Light, Custom

Color	5000K, 6500K, 7500K, Native, RGB Adjust
OSD	Language, OSD-Timeout, OSD rotation
Image adjust	Sharpness, Saturation, Hue, Expansion
Audio	Mute, Volume
Information	Model name, Serial number, Signal input, Resolution/mode, Display mode, Color Temperature, ACR Status, ABC Status
Picture in Picture (PIP)	Input, Mode, Position, USB Upstream, Swap
Advanced settings	Presence Sensor, Proximity Adjust, Daisy Chain, FreeSync, Overdrive, DDC/CI, Status LED, Power Button, Factory Recall
Power consumption (typical)	
Soft switch off	0.24 W
Power save mode	0.26 W
Operating with EPA settings	33.34 W
Total Energy Consumption (ETEC)	105.52 kWh/year
Operating maximum brightness	51 W
Power supply	integrated
Power notes	Speakers off, USB not connected ETEC and EPA refer to ENERGY STAR® 8.0 Power save mode according to EEI test conditions
Electrical values	
Rated voltage range	100 V - 240 V
Rated frequency range	50 Hz - 60 Hz
Protection class	1
Compliance	
Model	P34-9U
Global	ENERGY STAR® 8.0, TCO Certified Displays 8.0, EPEAT® Bronze (dedicated regions), Zero bright and dark pixel faults, Subpixel faults according to ISO9241-307 (Pixel fault class I), TÜV Flicker Free Certified, TÜV Low Blue Light Certified
Europe	Energy Efficiency Class: A, EN 60950, CE certification according to EC Directive 2004/108/EEC, RoHS, WEEE, IT-Eco-Declaration
Australia/New Zealand	(on customer request)
Germany	TÜV GS
Russia	EAC
Singapore	S-Mark
South Korea	KC, E-Standby
Taiwan	BSMI
USA/Canada	FCC Class B, cUL
Compliance link	https://sp.ts.fujitsu.com/sites/certificates
Dimensions / Weight / Environmental	
Dimension without stand (W x D x H)	814.82 x 109.39 x 372.8 mm 32.08 x 4.31 x 14.68 inch
Dimension with stand (W x D x H)	814.82 x 275 x 390.3 mm 32.08 x 10.83 x 15.37 inch
Weight (unpacked)	8.95 kg 19.73 lbs
Weight (Monitor only)	6.22 kg 13.71 lbs
Operating ambient temperature	5 - 35 °C
Operating relative humidity	15 - 85% (non condensing)
Miscellaneous	
Miscellaneous	VESA DDC/ CI, Flat Display Mounting Interface VESA MIS-D 100 C, Kensington lock prepared
Color	Matt black

Package content

Display delivered accessories	DisplayPort data cable 1.8 m HDMI cable 1.8 m USB cable 1m (USB-C to USB-C) USB-cable 1.8 m (USB-A to USB-B) Power cable for wall socket (Euro-Schuko-Type CEE7) 1.8 m Quickstart flyer Safety notes
Display delivered accessories notes	Power cable with IEC-60320-C13, 3-pin connector on display side Data cables and USB cable detachable on display User manual and DisplayView Software is available via download DisplayView Software is necessary for AutoPivot function and Presence Sensor PC security solution

Packaging information

Packaging dimension (mm)	935 x 325 x 500 mm
Packaging dimension (inch)	36.81 x 12.8 x 19.69 inch
Weight (packed)	12.65 kg
Weight (packed) (lbs)	27.89 lbs

Order information

Order Code	S26361-K1695-V160
EAN Code	4059595920589

Warranty

Warranty period	3 years (depending on country)
Warranty type	Collect & Return Service (depending on country specific requirements)
Warranty Terms & Conditions	http://www.fujitsu.com/warranty
Spare Parts availability	5 years after end of product life
Service Weblink	http://www.fujitsu.com/emeia/products/product-support-services/

More information

Fujitsu products, solutions & services

In addition to FUJITSU Display P34-9 US, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

Fujitsu Portfolio

Build on industry standards, Fujitsu offers a full portfolio of IT hardware and software products, services, solutions and cloud offering, ranging from clients to datacenter solutions and includes the broad stack of Business Solutions, as well as the full stack of Cloud offering. This allows customers to leverage from alternative sourcing and delivery models to increase their business agility and to improve their IT operation's reliability.

Computing Products

www.fujitsu.com/global/products/computing/

Software

www.fujitsu.com/software/

More information

Learn more about FUJITSU Display P34-9 US, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website.
www.fujitsu.com/emeia/products/computing/peripheral/displays

Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment. Using our global know-how, we aim to contribute to the creation of a sustainable environment for future generations through IT. Please find further information at <http://www.fujitsu.com/global/about/environment/>



Copyrights

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see <http://www.fujitsu.com/emeia/resources/navigation/terms-of-use.html>
Copyright 2020 Fujitsu Technology Solutions GmbH

Disclaimer

Technical data are subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.

Contact

Fujitsu Technology Solutions GmbH
Website: www.fujitsu.com
2020-05-19 EM-EN

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see <http://www.fujitsu.com/emeia/resources/navigation/terms-of-use.html>
Copyright 2020 Fujitsu Technology Solutions GmbH